FEB 2 7 2006

Listing of the Claims

The following listing of claims will replace all prior versions and listings of the claims in the application:

- 1. (Canceled)
- 2. (Canceled)
- 3. (Canceled)
- 4. (Canceled)
- 5. (Canceled)
- 6. (Canceled)
- 7. (Canceled)
- 8. (Canceled)
- 9. (Canceled)
- 10. (Canceled)
- 11. (Canceled)
- 12. (Canceled)
- 13. (Canceled)
- 14. (Canceled)

controller;

15. (Currently Amended) An alarm clock comprising: an alarm clock controller electrically connected to an electrical power source; at least one electrical connector electrically coupled to the alarm clock

at least one sensor operable to detect a presence of a user;

logic for monitoring the at least one sensor:

logic for recording a time between an activation of the at least one electrical connector and a detected absence of the user; and

logic for adjusting an activation time of the at least one electrical connector, wherein said alarm clock controller includes a circuit operable to switch electricity on and off to the at least one electrical connector, and wherein the adjustment to the activation time is based on a function of the recorded time.

APN: 10/49,620

- 16. (Previously Presented) The alarm clock of claim 15, further comprising a heat level controller electrically connected to the alarm clock controller and the at least one electrical connector.
- 17. (Previously Presented) The alarm clock of claim 16, wherein the heat level controller is adjustable to vary a flow of electricity to the at least one electrical connector when the electricity is switched on to the at least one electrical connector.
- 18. (Previously Presented) The alarm clock of claim 15, further comprising at least one heating device electrically coupled to the at least one electrical connector.
- 19. (Previously Presented) The alarm clock of claim 18, wherein the at least one heating device includes at least one of a heating pad or an electrically heated blanket.
- 20. (Previously Presented) The alarm clock of claim 18, wherein the heating device further includes one or more electrical switches operable to connect electricity to corresponding one or more zones of the heating device.
- 21. (Previously Presented) The alarm clock of claim 15, wherein the alarm clock controller includes a circuit to manually switch the at least one electrical connector for a period of time.
- 22. (Currently Amended) The alarm clock of claim 15, further comprising sensors operable to detect a presence of a user, and wherein the at least one electrical connector is deactivated when the user is not present.
- 23. (Currently Amended) The alarm clock of claim 15 claim 22, wherein: further comprising:

logic for monitoring the sensors;

logic for recording a time between the activation of the at least one electrical connector and a detected absence of the user; and

logic for adjusting an activation time of the at least one electrical connector the function is based on an average time a user wakes after the activation of the at least one electrical connector.

APN: 10/49,620

Page 3 of 9

Response to Office Action Dated Dec. 5, 2005

24. (Currently Amended) A thermal alarm clock comprising:

an alarm clock controller;

a heat level controller in electrical connection with the alarm clock controller; at least one heating device electrically connected to the alarm clock controller; at least one sensor operable to detect a presence of a user:

logic for monitoring the at least one sensor;

logic for recording a time between the activation of the at least one heating device and the absence of a user;

logic for adjusting the activation time of the at least one heating device; and wherein said alarm clock controller activates and deactivates said at least one heating device by switching electricity on and off to said at least one heating device, and wherein the adjustment to the activation time is based on a function of the recorded time.

- 25. (Previously Presented) The thermal alarm clock of claim 24, wherein the at least one heating device wherein the at least one heating device includes at least one of a heating pad or an electrically heated blanket.
- The thermal alarm clock of claim 24, wherein the 26. (Previously Presented) heating device further includes one or more electrical switches operable to connect electricity to corresponding one or more zones of the heating device.
- 27. (Previously Presented) The thermal alarm clock of claim 24, wherein the heat level controller includes a circuit operable to variably adjust a flow of electrical power to the at least one heating device when the alarm clock controller activates the at least one heating device.
- 28. (Previously Presented) The thermal alarm clock of claim 24, wherein the alarm clock controller includes a circuit to manually activate the at least one heating device for a period of time.

APN: 10/49,620

- 29. (Currently Amended) The thermal alarm clock of claim 24, further comprising a plurality of sensors operable to detect a presence of a user, and wherein the at least one heating device is deactivated when the user is not present.
- 30. (Currently Amended) The thermal alarm clock of claim 24 claim 29, wherein further-comprising:

logic for monitoring the sensors;

logic for recording a time between the activation of the at least one heating device and the absence of a user; and

logic for adjusting the activation time of the at least one heating device the function is based on an average time a user wakes after the activation of the at least one heating device.

- 31. (Previously Presented) The thermal alarm clock of claim 24, wherein the alarm clock controller includes at least one electrical connector and the at least one heating device is electrically connected to the alarm clock controller through the at least one electrical connector.
- 32. (Currently Amended) A method for waking a user comprising: selecting an initial activation time in an alarm clock controller; and detecting a presence of a user; selecting a wake time occurring after the initial activation time; recording a time between the initial activation time and a detected absence of the user:

activating at least one heating device at the in initial activation time, the at least one heating device being electrically coupled to the alarm clock controller; and automatically selecting a subsequent activation time of the at least one heating device based on a function of the time.

33. (Previously Presented) The method of claim 32, wherein the at least one heating device includes at least one of a heating pad or an electrically heated blanket.

- The method of claim 32, wherein the heating device 34. (Previously Presented) includes a plurality of electrical switches operable to connect electricity to corresponding zones of the heating device.
- The method of claim 32, further comprising varying a 35. (Previously Presented) flow of electricity to the at least one heating device when the alarm clock controller activates the at least one heating device.
- The method of claim 32, wherein the at least one 36. (Previously Presented) heating device is activated for a preselected period of time at the initial activation time.
- The method of claim 32, further comprising manually 37. (Previously Presented) activating the at least one heating device for a preselected period of time.
- 38. (Canceled)
- The method of claim 32 claim-38, wherein the at least 39. (Currently Amended) one heating device is deactivated if the user is not present.
- The method of claim 32 claim 38, wherein further 40. (Currently Amended) comprising:

selecting a wake time occurring after the initial activation time; determining an average time between the initial activation time and a detected absence of the user;

automatically selecting a subsequent activation time of the at least one heating device the function of the time is an based on the average of the time between the activation time and the detected absence of the user.